



# **QTRam**®

## **Portable Raman Spectrometer for Content and Blend Uniformity**



The QTRam®, powered by B&W Tek's STRaman® technology, is a portable transmission Raman spectrometer that allows for rapid and nondestructive quantitative analysis ideal for blend and content uniformity testing of finished products such as tablets and capsules. The unit can be easily operated using 21 CFR Part 11 compliant software for quantitative analysis on the inbuilt tablet computer, while the portable form factor allows users to use it for at-line analysis or in the lab.

## **Applications:**

**Content uniformity** - ensure the dosage uniformity of the API in solid-dosage finished products including tablets, capsules, and gels

**Blend uniformity** – assess adequacy of mixing to ensure blend uniformity and homogeneity

**Formulation development** - support QbD initiatives in quantifying API and excipient concentrations in finished dosage forms

**Counterfeit detection** – calculate API quantity to ensure correct drug and correct dosage

#### **Features:**

- Versatile STRaman technology with high sensitivity and high-throughput for see-through, transmission, or conventional Raman spectroscopy
- Easy-to-use 21 CFR Part 11 compliant software for quick results and reporting
- Portability for at-line or laboratory analysis
- Customizable sample holders to accommodate any sample dimension
- Step-by-step, easy-to-follow quantitative modeling and method development

#### **Benefits:**

- Rapid quantitative results in seconds
- One system for multiple applications
- Quantitative sample composition, crystallinity and polymorphic form from single measurement over large sample volume
- No sample preparation
- No consumables
- No disposal cost
- USP-recognized transmission Raman for content and blend uniformity applications


### **Specifications:**

Model	BWS475-785H-CU	
Laser Source	785 nm, full power >340 mW at sample with software adjustable power	
Software	21 CFR Pt. 11 Compliant BWAnalyst™	
System Configuration	Transmission Raman	
Power Options		
Power Adaptor	Input: 100-240V AC 50/60 Hz, Output: 12VAC @6.6 Amps	
Physical	Main Unit	QT-Sampler®
Dimensions	15.7 in x 10.2 in x 9.8 in (40 cm x 26 cm x 25 cm)	13.01 in x 6.68 in x 6.97 in (33 cm x 17 cm x 18 cm)
Weight	~19.5 lbs (~8.8 kg)	~17.81 lbs (~8.5 kg)
Operating Temperature	0 °C – 35 °C	
Humidity	10% - 85%, non-condensing	

#### **Software:**

B&W Tek offers comprehensive software packages that provide solutions for Raman application needs. Powerful calculations, easy data management, and user-friendly, easy-to-follow workflows are all at the tips of your fingers.

BWAnalyst™ is the touch-screen-operated 21CFR part 11 software with a logical workflow for data acquisition, method building, routine analysis and reporting. Once the method is developed and validated, operators can quickly perform quantitative predictions, getting clear results in seconds that are stored in a secure database. The software has configurable reports, with electronic signatures and a full audit trail.



## **System Includes:**

- QT-Sampler and two standard sample holders
- Fiber-optic see-through Raman sampling kit
- Laser safety goggles
- BWAnalyst 21CFR Part 11 compliant software
- BWSpec® operating software for exploratory work
- BWIO® chemometric software
- Probe holder BAC150B



19 Shea Way, Newark, DE 19713, USA • Tel: +1 (302) 368-7824 • Web: www.bwtek.com